



Art-Nr. Part No.	Passend zu: Siutable for:	d h11	g	a	b	l1	l2	l3	Gewicht kg per 100 Weight kg per 100
ES-4x8-VZ	GK-4x8-VZ	4	8	9.5	11.1	19	15	4.5	0.145
ES-5x10-VZ	GK-5x10-VZ	5	10	12	13.7	23	19	5.5	0.254
ES-5x20-VZ	GK-5x20-VZ	5	20	12	13.8	33	29	5.5	0.31
ES-6x12-VZ	GK-6x12-VZ	6	12	14	16.2	28	23	6.5	0.458
ES-6x24-VZ	GK-6x24-VZ	6	24	14	16.3	40	35	6.5	0.516
ES-8x16-VZ	GK-8x16-VZ	8	16	19	21.6	37	30	8	1.059
ES-8x32-VZ	GK-8x32-VZ	8	32	19	21.6	52	46	8	1.155
ES-10x20-VZ	GK-10x20-VZ	10	20	23	26	46	38	10	1.938
ES-10x40-VZ	GK-10x40-VZ	10	40	23	26.3	66	58	10	2.046
ES-12x40-VZ	GK-12x24-VZ	12	24	28	31.1	53	45	12	3.306
ES-12x48-VZ	GK-12x48-VZ	12	48	28	31.2	78	69	12	3.5
ES-14x28-VZ	GK-14x28-VZ	14	28	31	34.1	62	52	14	4.722
ES-14x56-VZ	GK-14x56-VZ	14	56	31	34	92	82	14	5.076
ES-16x32-VZ	GK-16x32-VZ	16	32	36	39.5	73	62	16	6.94
ES-16x64-VZ	GK-16x64-VZ	16	64	36	39.2	103	92	16	7.44
ES-20x40-VZ	GK-20x40-VZ	20	40	45	50	87.5	71.5	16	13

Werkstoff:

- Bolzen aus, Stahl verzinkt, Feder aus Federstahl

Oberfläche:

- Galvanisch verzinkt (blau/weiß)

Material:

- Bolt, carbon steel, Spring, Spring steel

Surface:

- Zinc plated (blue/white)